

MAJAR



L'accessoire essentiel

Sanding



Under the specific lawn care operations, sanding has a high importance with several goals:

- fight against thatch and soil (direct complement for aeration)
- lawn flatness
- protection of lawn (area on soil surface between airy and underground)

Sand is the division element. It improves the permeability for air and water. Rugby and football fields are better protected against the shoe spikes before and during winter.



2 linkage versions for spreading: Hitched or semi-mounted.

S400RL / S700RL :
Hitched – drawbar eye

S400SP / S700SP :
Semi-mounted – 3 point linkage
- mechanical decoupling from tractor
- flow control by toothed rack

Low pressure tyres 0,5 bars, width 31 cm
Working width 1 m or 1,5 m

Option

Double-action hydraulic cylinder for loading



CHARACTERISTICS

Reference	Capacity (L)	Working width (cm)	Overall width (cm)	Overall length (cm)	Overall height (cm)	Tare weight (Kg)	Overall laden weight (Kg)	Recommended power (HP)
S400 RL	450	100	193	227	160	290	1100	20
S400 SP	450	100	193	131	160	290	1100	20
S700 RL	700	150	243	227	160	330	1500	25
S700 SP	700	150	243	131	160	330	1500	25

MAJAR

1, Route de Montréal - CS 30074 - 11890 Carcassonne Cedex 9

E-mail: commercial@majar.fr - Tél.: 04 68 72 83 11 - Fax: 04 68 72 51 61