

MAJAR



L'accessoire essentiel

Hinged and removable sideboards in lateral position.

Parking brake

Hitch with adjustable height. Hydraulic braking on RMTB2225.

RMTB1020 : stand, without lighting, tongue demountable, turning ring Ø32 reflector signs



Models comply with braking legislation
Serial hitch with adjustable height.

Transport

Trailers for garden tractors, compact tractors, tiller ranges
Tipping trailer for compact tractor

TRAILER HINGED SIDEBOARD

Payload kg	Length plateforme (cm)	Width plateforme (cm)	Height (cm)	Wheels	Height under drawbar (cm)	Weight (Kg)	
1 000	200	120	35	600-9 - 10 plis	38 à 55	280	RMTB1020
1 084	250	130	35	185 x14	20 à 55	415	RMTB1425
1 067	250	130	35	225x70R15	23 à 58	432	RMTB2225

Options :

	Weight (kg)	
Hand pump 4 l	8	RMTBPM
Jockey wheel for RMTB1020	5	ROUERTB
Electric kit for RMTB1020	6	KERMTB
Coupling Ø 42 for RMTB1020		582231
Rotating ring Ø 42 on RMTB1020		ATTEL42
Mesh extension panel 100 cm for RMTB1020	75	RGM1020
Mesh extension panel 100 cm for RMTB1425 and 2225	85	RGM1025



RMTB1425 + RGM1025

Monocoque trailer compact tractor

RMTB 1425M-2225M : jockey wheel, road lighting, back buffer twofold articulation, rotating ring Ø 42.

HYDRAULIC MONOCOQUE TIPPING TRAILER

Payload kg	Length plateforme (cm)	Width plateforme (cm)	Height (cm)	Wheels	Height under drawbar (cm)	Weight (Kg)	
1 084	250	130	40	185x14	20 à 55	415	RMTB1425M
1 067	250	130	40	225x70R15	23 à 58	432	RMTB2225M



RMTB1425M

Parking brake – jockey wheel – road lighting
Back buffer twofold articulation – Hitch with adjustable height
hydraulic braking on RMTB2225M

Option :

	Weight (Kg)
Mesh extension panel 100 cm for RMTB1425M and 2225M	90 RGM1025M

Tipping trailers compact tractors



RMT700

Equipment : hinged and removable sideboards
 Rotation drawbar eye

TIPPING TRAILERS FOR COMPACT TRACTORS

Payload kg	Length plateforme (cm)	Width plateforme (cm)	Height (cm)	Wheels	Height under drawbar (cm)	Weight (Kg)	
700	150	100	28	16x6,50-8	34 - 50	32 110	RMT700
1000	200	120	35	600-9 - 10 ply	35	32 145	RMT1000

Options :

Mesh extension panel for RMT 700	Height 50 cm	38	RGM515
RMT 1000	Height 100 cm	75	RGM1020
Electric kit road for RMT 1000		6	KERMT
Jockey wheel for RMT 1000		4	ROUERM

Exists also for ball coupling Ø50



RMT1000

Combined loaders

	Weight (Kg)	
Bale spear 3 point linkage	45	PIQBOT936
Fork guide set for pallets	10	PIQPALET936

Lifting capacity: 330 kg on the fork top / 500 kg split load
Base : PIQBOT936 : bale spear 3 point linkage cat.1, 2 spades Ø 36, usable length 93 cm, conical fitting.

Accessories:

PIQPALET936 : fork guide set for pallets to mount on PIQBOT936.
 2 blades 9 cm x 94 cm

Registered design

PIQBOT936
 + PIQPALET936



PIQBOT936



Tipping trailer garden tractor

Elevated – wheels under chassis – tipping – mesh extension panel optional

REMOVABLE SLIDING REAR LIFTGATE - PAYLOAD 340 KG

Plastic rims – wheel Ø 400 x 80 110 x 80 cm (85 overall) x 30 cm (H) - monobloc Wheel Ø 400 x 80 (spare part)	Weight (Kg)	
	44	RA340
	2	082252
Aluminized rims - wheel Ø 377 x 160 110 x 80 cm (89 overall) x 30 cm (H) - monobloc Wheel Ø 377 x 160 (spare part)	45	RA350
	3,5	082373



RA340



RA350

REMOVABLE PIVOTING REAR LIFTGATE - PAYLOAD 500 KG

Alluminized metallic rims - wheels Ø 400 x 160 120 x 100 cm (120 overall) x 40 cm (H) - monobloc Wheel Ø 400 x 160 (spare part)	Weight (Kg)	
	92	RA410
	4	082374
Options :	Weight (Kg)	
Mesh extension to clip perforated sheet 110 x 80 x 45 cm (H) for RA340 and 350	16	RG310
120 x 100 x 45 cm (H) for RA410	25	RG410



RA410 + RG410

SIDEBORD PLATEFORM - PAYLOAD 700 KG

Wheels Ø 16 x 6,50 - 8 150 x 100 (105 overall) x 28 cm (H) Sideboard and back hinged and removable Front buffer removable	Weight (Kg)	
	123	RA710
Option :		
Mesh extension removal	Height 50 cm	38 RGM515



RA710

Height adjustment allows to couple horizontally and increases traction force.

Trailer for tiller range

Braked - parking brake - tipping - reflector signs
adjustable confort seat - delivered without connection

TRAILER FOR TILLER RANGE

	Weight (Kg)	
MONOBLOC 120 X 100 (122 overall) x 40 cm pivoting back door removable payload 500 kg - wheels Ø 16 x 6,50-8	105	RMO400
Option : mesh extension panel 120 x 100 x 50 cm	25	RG410
PLATEAU 150 X 100 (105 overall) x 28 cm Sideboard and back hinged and removable Front buffer removable. Payload 600 kg Wheels Ø 16 x 6,50-8	125	RMO600
Option : mesh extension panel Height 50 cm		RGM515
PLATEAU 200 X 120 (122 overall) x 35 cm Hinged and removable sideboards Payload 800 kg - wheels 600 x 9-10 plis	160	RMO800
Option : mesh extension panel Height 100 cm	75	RGM1020
CONNECTING ELEMENT : for compact tractors with drawbar load		
Height 74 or 95 and a pin Ø 16		081781
For tiller range KUBOTA TF100 and STAUB 600-7000 Ø16		582182
For tiller range STAUB PPX and 9500D Ø25		582183
For tiller range STAUB CHALLENGER		582184
For tiller range GOLDONI BINGO, JOLLY and 58I Ø 19,5		582185
For tiller range BOUYER 223		582186
For tiller range GOLDONI 140		
Spécial Lux DE and FORT Minitigre and Supertigre		582187
For tiller range GRILLO G55-G85-107 Ø 14,5 - H 42		582246



RMO400 + 081781



RMO600 + 582183



RMO800 + 081781

Tipping trough for compact tractor

BENNES ARRIÈRE BASCULANTES

		Weight (Kg)	
LIGHT MONOBLOC REAR TROUGH : payload 250 Kg Removable door - easy pivoting	115x64	75	BAL115
REAR TROUGH TO MOUNT : payload 400 Kg double articulation	100x63	75	BA100
autoloader	125x63	100	BA125



BA100
REINFORCED MONOBLOC



BAL115
MONOBLOC LIGHT

